ViewSonic® VE702m LCD Display

17” TFT LCD Display

Attractive and affordable

The 17” LCD display VE702m impresses with its aesthetic exterior and strong performance. Good brightness and contrast values deliver **SHARP IMAGES AND VIVID COLOURS**. The **ULTRA-FAST 14MS RESPONSE TIME** ensures even action-packed films and fast-moving games are presented with the fluidity they deserve. Loudspeakers integrated in the bezel provide the sound to accompany the visuals. Thanks to these and many more useful features, the VE702m is an ideal LCD display for home entertainment, small/home office, corporate, government or educational purposes.

Distinctive design, affordable value.

Stylish bezel design

The full 17" viewable screen lets you see more without taking up valuable desktop real estate.

High brightness and contrast

350 cd/m² brightness (typ) and 350:1 contrast ratio (typ) for rich, detailed images.

1280x1024 resolution

ClearMotiv™ Technology

Ultra-fast 14ms video response enables video at 71.4 FPS.

Business Audio (1w x2)

OnView® controls plus short cuts for superior screen adjustability

Screen adjustments are precisely made via an easy-to-use on-screen menu.

VESA® 75mm wall mount compliant

sRGB colour management

For a closer match of image display to print outs.

PC and MAC® compatible

TCO’99 qualified

ViewSonic®

Reliable Value

ViewSonic® VE702m LCD Display

17" TFT LCD Display

17" TFT LCD DISPLAY WITH ON-SCREEN MENU

LCD PANEL	**Type**	17" Colour TFT Active Matrix SXGA LCD, TN Technology
	Display Area	338mm horizontal x 270mm vertical
	Optimum Resolution	1,280 x 1,024 @ 60Hz
	Pixel Pitch	0.264mm
	Contrast Ratio	350:1 (typical)
	Viewing Angle	160° horizontal, 120° vertical (@ 10:1)
	Response Time	14ms (typical)
	Brightness	350cd/m² (typical)
	Glass Surface	Anti-glare
	Backlight Life	50,000hrs (typical)
VIDEO INPUT	**Analogue**	RGB Analogue (75 ohms, 0.7Vp-p)
	Frequency	F_h: 30-82kHz, F_v: 56-76Hz
	Sync	H/V Separated (TTL)
COMPATIBILITY	**PC**	PC and compatibles (from VGA up to 1,280 x 1,024)
	Macintosh®[1]	Power Mac™ (up to 1,280 x 1,024)
AUDIO	**Speaker**	1w x2
	Amplifier	1w @THD <10%
CONNECTORS	**Analogue**	15 pin mini D-sub x1
	Audio	Stereo Mini Audio Line in
POWER	**Voltage**	AC 100-240V (50/60Hz), auto switch, external power supply
	Consumption	60 Watt (max.)
CONTROLS	**Physical**	Power (Soft), Auto/Exit, Turbo, Brightness +/-, Contrast +/-, Menu
	OSD	Auto Image, Adjust [Contrast, Brightness, Colour Adjust (sRGB, 9300K, 7500K, 6500, R, G, B)], Manual Image Adjust [H. Position, V. Position, Fine Tune, Sharpness, Setup Menu [Language, Resolution Notice, OSD Position, OSD Timeout, Memory Recall]
OPERATING CONDITION	**Temperature**	0°C to 40°C
	Humidity	10% to 90% (no condensation)
DIMENSIONS		387mm (W) x 403mm (H) x 213mm (D)
WEIGHT	Net	3.4kg
REGULATIONS		TCO'99, TÜV/GS, CE, UL, c-UL, CB Report, FCC-B, Energy Star, NOM, ISO13406-2, GOST-R, HYGINIC,
POWER MANAGEMENT		TCO'99, ENERGY-Standards
WARRANTY		Please see: http://www.viewsoniceurope.com/UK/Support/warranty.htm

specifications

ISO 9001 FM 40187 ISO 14001 EMS 40968

ViewSonic Corporation's QMS\EMS has been registered to ISO 9001 & ISO 14001 by the British Standards Institution.

ViewSonic®

ViewSonic Europe Limited/UK
ViewSonic House
Fleming Way, Crawley
West Sussex, RH10 9GA
United Kingdom

Tel: +44 (0) 12 93 64 39 00
Fax: +44 (0) 12 93 64 39 10

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
Parc des Barbanniers
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Benelux	Tel: +32 056/85 26 27
ViewSonic Denmark	Tel: +45 70 22 11 71
ViewSonic Finland	Tel: +358 (9) 54 06 40 70
ViewSonic Italy	Tel: +39 02 5832 0356
ViewSonic MEA	Tel: +971 (0) 4 88 11 871
ViewSonic Norway	Tel: +47 (0) 22 88 17 60
ViewSonic Spain	Tel: +34 (0) 91 63 05 339
ViewSonic Sweden	Tel: +46 (0) 8 50 71 30 00

[1] May require optional Mac adapter.

Copyright © 2004, ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. VS VE702m-11/04-UK

For more product information, visit us on the web at www.ViewSonicEurope.com